

2

AMENDMENT 2
INCREASED PROJECT AREA TO INCLUDE
ROAD WIDENING TO SOUTH OF
DOMINGUEZ LOOP ROAD AND ROAD
IMPROVEMENTS ON WEST SIDE OF
SIERRA COLLEGE BOULEVARD.

SIERRA COLLEGE BOULEVARD

SCHRIBER WAY

DOMINGUEZ
LOOP ROAD

CONSTRUCTION TRAILER, MATERIAL
STORAGE/STAGING, VEHICLE
MAINTENANCE AND FUELING AND
CONCRETE WASHOUT. LOCATION
TO BE FIELD DETERMINED.

PLACE SILT FENCE
AT EDGE OF
CONSTRUCTION

PLACE STRAW ROLL AT TOP
AND TOE OF SLOPE AND
EVERY 20' ALONG SLOPE.

PLACE SILT FENCE
AT EDGE OF
CONSTRUCTION

PLACE HYDROSEED, STRAW MULCH AND
TACKIFIER ON ALL EXPOSED SOILS
ONCE GRADING IS COMPLETE.

PLACE DRAIN INLET
PROTECTION

CONSTRUCT DOUBLE
ROCK CHECK DAM

PLACE SILT FENCE
AT EDGE OF
CONSTRUCTION

PLUG
GRADED
INLET

PLACE DRAIN INLET
PROTECTION (TYP.)

TEMPORARY BERM

PLACE SILT FENCE
AT EDGE OF
CONSTRUCTION

DISCHARGE LOCATION
AND SAMPLE POINT

PLACE STRAW ROLL AT TOP
AND TOE OF SLOPE AND
EVERY 20' ALONG SLOPE.

PLACE GRAVEL BAG
BERM ALONG FACE
OF CURB

PLUG INLET TO PROPOSED CULVERT AND PUMP
ANY INCOMING FLOW INTO THE TEMPORARY
HOLDING BASIN AT THE INLET NORTH OF
DOMINGUEZ LOOP.

PLACE GRAVEL BAG BERM ALONG SWALE
AND AT EACH END OF CULVERT.

PLACE SILT FENCE AT EDGE
OF CONSTRUCTION

CONSTRUCTION
ENTRANCE

HYDROSEED NOTE:
ALL EXPOSED SOILS THAT ARE
IN-ACTIVE FOR MORE THAN 14
DAYS ARE TO RECEIVE
HYDROSEED, STRAW MULCH,
AND TACKIFIER.

STRAW MULCH NOTE:
ALL EXPOSED SOILS SHALL
RECEIVE STRAWMULCH AND
TACKIFIER PRIOR TO ANY
FORECAST RAIN EVENT.

LIMIT OF
CONSTRUCTION
TOTAL DISTURBED
AREA = 4.1 AC.

2

PLACE STRAW ROLL AT TOP
AND TOE OF SLOPE AND
EVERY 20' ALONG SLOPE.

PLACE SILT FENCE
AT EDGE OF
CONSTRUCTION

PLACE HYDROSEED, STRAW MULCH AND
TACKIFIER ON ALL EXPOSED SOILS
ONCE GRADING IS COMPLETE.

INCOMING RUN-ON FROM
NORTHWEST. IF RUNON IS
ANTICIPATED TO CROSS AN AREA OF
EXPOSED SOIL, PROVIDE A
DIVERSION AROUND EXPOSED AREA
OR PROVIDE A STABILIZED FLOW
PATH OVER EXPOSED SOIL.

PLACE STRAW ROLL AT TOP
AND TOE OF SLOPE AND
EVERY 20' ALONG SLOPE.

CONSTRUCTION
ENTRANCE

PLACE GRAVEL BAG
BERM ALONG SWALE
AND AT EACH END
OF CULVERT.

PLACE STRAW ROLL AT TOP
AND TOE OF SLOPE AND
EVERY 20' ALONG SLOPE.



DOMINGUEZ LOOP ROAD
ROCKLIN, CA

FIGURE 3
POST-DEVELOPED SITE PLAN

PROJECT NO.:001-017 DATE: 07/16/2013 SHEET NO. 2 OF 2